


Flail mower

- Park Ranger 2150



Standard equipment:

Clearing height adjustment The clearing height is adjusted using the two forward wheels (rough and fine adjustment). Rough adjustment using seven adjusting rings in interval 0-110 mm. Fine adjusting carried out by a variable-adjustable lever.

Extra equipment (options):

Verticutter knives Changing the flails with vertical blades converts the flail mower into a verticutter, which deals with moss and weeds without the need for pesticides. The verticutter removes moss while simultaneously cutting a thin score in the turf, so the grassroots are aired. This strengthens the grass so the turf is much more resilient to weeds.

Counterweight It is recommend to use a counterweight on the back of the Park Ranger 2150 when using the flail mower. (2 x 18,5 kg)

Radiator cover It is recommend to use a radiator cover for mowing in very dry grass and dusty surroundings, as this stops the radiator from becoming choked with grass and protects the motor.

Technical specifications

Dimensions		
Length	mm	2895
Width	mm	1475
Height with / without cabin	mm	1935 / 1210
Storage dimensions		
Length	mm	955
Width	mm	1475
Height	mm	435
Weight		
Weight (flail mower / verticutter)	kg	154 / 151
Performance		
No. of flails	pcs.	76
No. of vertical blades (max.)	pcs.	38
Flail - clearing width	mm	1226
Flail - clearing height	mm	1-110
Rotation of blades	rpm	2800
Verticutter - clearing width	mm	1172
Verticutter - clearing depth	mm	0-15
CE certified according to EU directive		

