

Salt and sand spreader

- Park Ranger 2150

Standard equipment:

Durable material All parts that get in contact with salt and sand are rust

free, made of synthetic material or stainless steel.

Stirrer The stirrer prevents blocking, crushes lumps and ensures precise and uniform spreading - and thereby even

thawing of the ground. Made of hardened Hardox steel the stirrer fingers are extremely robust.

Material storage There is space for extra bags of salt and sand on top

of the hopper grate, enabling the operator to fill the salt and sand spreader on site. Please note the maximum $\,$

loading capacity.

Stand A stand for attaching/detaching is delivered with the

spreader as standard. The stand has wheels, making it easy to move the spreader into storage without heavy

iii tirig.

Tarpaulin cover A cover keeps the material dry and thereby indirectly

improve the spreading accuracy.

Extra equipment (options):

Auger cover for vacuum salt The cover ensures that tiny material such as vacuum salt, does not just run out of the spreader, which reduces the waste and increase the operation efficiency.







2510 mm

Technical specifications

-					
- I)	im	Δn	CI	a	ne

A		1
CE certified according to EU directive		
Operating speed	km/h	1-16
Spreading width	mm	1000-5000
Performance		
Loading height	mm	1250
Spreader load, max.	kg	350
Volume	I	210
Spreader		
	1 9	
Weight of stand	kg	31
Weight (spreader)	kg	97
Payload with cabin	kg	440
Weight with cabin 1)	kg	860
Weights		
Treight with stand	111111	1330
Height with stand	mm	1350
Width	mm	800
Length with stand	mm	1175
Storage dimensions		
Height with cabin	mm	1935
Width	mm	1015
Length	mm	2510

¹⁾ Includes: salt and sand spreader, 75 kg driver and 90% fuel capacity





