

Snow plough

- City Ranger 3070





4257 mm

Standard equipment:

Hydraulic angle adjustment

The snow plough angle can be adjusted from the controls inside the cabin, making it easy for the operator to adjust the blade when needed.

Safety tilt system

When operating in deep snow there is a risk of hitting obstacles. The safety tilt function reduces the risk of damages both to the snow plough and surroundings.

Adjustable weight distribution

The automatic weight distribution makes the snow plough suitable for clearing gravel paths as well.

Floating skids

The 2 skids are height adjustable and ensure that the blade follows ground variations

Vulkollan scraper edge

The vulcanised rubber scraping edge is good for surfaces that require extra care. The scraper edge can be turned and used on two sides giving double usage and extended lifetime. The snow plough can be mounted with either vulcanised rubber scraper or steel scraper.

Steel scraper edge

The scraper edge can be turned and used on two sides giving double usage and extended lifetime. The snow plough can be mounted with either steel scraper or vulcanised rubber scraper.

Indication reflexes

Reflexes marking the edge of the snow plough increases the safety for both snow plough and surroundings.

Extra equipment (options):

Indication flags

Flags marking the edge of the snow plough allows for precise positioning and increases the safety for both snow plough and surroundings (incl. flex pole).

Side position lights

Side position lights increase the visibility of the snow

plough.

Support wheels

Designed to operate at higher speeds. Operation is more quiet than with skids and they have less wear reducing each.

reducing (

Turf tires 1)

Though they are named turf tires they are also excellent for winter driving. The way the thread pattern is designed means you will have a minimum of snow build up in the tire thread. This allows for a good traction when driving in snow.

Winter tires (15") with snow chains 1)

Can be useful in snowy conditions, on steep hills or icy surfaces. The chains provides a better grip and increase the efficiency of the operation.

Technical specifications

CE certified according to EU directive

Dimensions		
Length	mm	4257
Width	mm	1500
Height / with beacon	mm	2000 / 2210
Storage dimensions		
Length	mm	700
Width	mm	1500
Height	mm	650
Weight		
Weight (snow plough)	kg	183
Performance		
Clearing width - straight	mm	1500
Clearing width - inclined	mm	1360
Ground clearance below scraper	mm	390
Operating speed	km/h	1-30
Handling snow depth up to	mm	400
Turning angle		25°
Theoretical performance	m²/h	40800

Type approval of the machine does not include turf tires and 15" winter tires with snow chains.





