# EGHOLM

## Triplex rotary mower 2500 - City Ranger 3070



#### **Standard equipment:**

| Hydraulic controlled<br>cutting wings | From the joystick in the cabin, the wings of the cutter<br>can be adjusted according to your needs: both wings<br>up, down or individual positions. Thereby, the cutting<br>width can be adjusted to the task when you have a<br>narrower space or when a larger lawn needs to be<br>mowed. The possibility of making the width smaller<br>with wings in an upright position is also an advantage<br>during transport to and from the task. |
|---------------------------------------|---|
| Hydraulic tipping<br>function         | From the joystick in the cabin, the cutter can be tipped<br>for easy cleaning and maintenance of the cutter or, if<br>wished, a change of blades.   |
| Manual height<br>adjustment           | The cutting height can be adjusted by moving the height rings on each of the wheels on the mower.   |
| Specially developed<br>blades         | The cutter is as standard equipped with specially developed 4-in-1 blades which ensure a nice cutting result.   |
| Piano wheels                          | Piano wheels (6 pcs.) move the cutter in line with the manoeuvring.   |
| Reverse function                      | The machine provides the absolute best conditions<br>for air supply and cooling by means of temporary air<br>reversal through the cooling unit, which blows away<br>any grass inside the intake grid.   |

#### Extra equipment (options):

"Low lift" blades The blades can be replaced with "Low lift" knives, which due to their design, give smaller bio cuts. Suitable for cutting short grass and used in dry conditions.

### **Technical specifications**

| Dimensions                             |       |             |
|--|-------|-------------|
| Length                                 | mm    | 5047        |
| Width                                  | mm    | 1880-2535   |
| Height / with beacon                   | mm    | 2000 / 2210 |
| Storage dimensions                     |       |             |
| Length                                 | mm    | 1550        |
| Width                                  | mm    | 1880-2535   |
| Height                                 | mm    | 500         |
| Weight                                 |       |             |
| Weight (rotary mower)                  | kg    | 365         |
| Performance                            |       |             |
| Ground clearance below mower           | mm    | 250         |
| No. of mower blades                    | pcs.  | 5           |
| Cutting width, both wings down         | mm    | 2480        |
| Cutting width, one wing down           | mm    | 2007        |
| Cutting width, both wings up           | mm    | 1533        |
| Adjustable cutting height              | mm    | 30-80       |
| Theoretical mowing area                | m²/h  | 24800       |
| Max. recommended operating speed       |       |             |
| Rotary mower *                         | km/h  | 10          |
| * Depends on grass and height          |       |             |
| Noise level                            |       |             |
| Noise level - outside LwA (2000/14/EC) | dB(A) | N/A         |
| CE certified according to EU directive |       |             |





