

# KV552

V-BLADE



- Cut Through Deep Snow
- Put Snow Where You Want It
- Hydraulic Angle Control
- Full Trip Blade

## V-BLADE

Model	KV552
Stock Code	39.55271
Required 12 Volt Switch/Plug Kit for 4500 Tractor	70.4104
Hydraulic Power Angle	Independent cylinders
Blade Wing Selection	Electric Solenoid
Spring Trip	Mechanical On/Off
Max Wing Angle (Left/Right)	30 Degrees
Adjustable Skid Shoes	Standard

### Optional Accessories

Top Deflection Flap	70.8044
Flare Kit, 12/6 inch extension (31/15 cm)	70.8046
Straight Extension Kit, 6 inch (15 cm)	70.8047
Polyurethane Cutting Edge	70.8048

### Dimensions

Length, Wings Back	38 inches (96 cm)
Length with 4000 Series Tractor	105.75 inches (269 cm)
Width, Wings Back	48 inches (122 cm)
Width, Wings Straight	55 inches (140 cm)
Width, Wings Forward	48.5 inches (123 cm)
Height	24 inches (61 cm)
Weight	240 lbs (109 kg)

All specifications subject to change without notice or obligation

## STANDARD FEATURES

- Hydraulically angle either wing (Requires 12 Volt Switch Plug Kit)
- Adjustable cast iron skid shoe discs
- Adjustable Spring controlled trip mechanism
- Trip Lockout Pin for Digging in material
- Reversible, Changeable Cutting Edge
- Center mounted skid shoe

## Optional Accessories

- Top Deflection Flap
- 1½ inch Flare Extension kits
- Polyurethane Cutting Edge
- 6" Straight Ext Kit



## HYDRAULICALLY ANGLE EITHER WING



The 55-inch wide Ventrac KV552 V-Blade maximizes efficiency with the ability to quickly change from V-plow to scoop to straight blade, all from the convenience of Ventrac's exclusive S.D.L.A. Control System. With a 48" V width, the KV552 is ideal for walks and areas that larger blades are unable to plow.

Standard features include hydraulically activated wing cylinders, mechanical trip, adjustable cast iron skid shoe discs, reversible high carbon hardened steel cutting edges, and a center shoe for gliding over rough terrain. Pivot points are fully greasable to ensure proper operation, even in the worst environments.

TRACTOR COMPATIBILITY KEY:

