For Earth, For Life

KUBOTA PROFESSIONAL MOWER RANGE



#Range

The power of total control

Kubota high-performance mowers for lawn and property maintenance are designed to meet all the tasks and requirements of professional users, from municipalities, sports facility operators to gardening companies and many more. From ride-on and zero-turn mowers, with or without grass collector, to front mowers – each with a wide variety of options – Kubota is certain to have the right solution for you.



G-Series ride-on mowers

When it comes to performance, speed and cutting quality, the new G-Series from Kubota clearly outperform comparable mowers. These machines are best in class in several important areas: driving

and mowing speed, as well as how quickly you can open and lift the grass collector.

ZD and GZD-Series zero-turn mowers

The GZD-Series zero-turn mowers combine exceptional maneuverability with an extremely efficient direct grass collection system with low or high discharge. Their exclusive Glide Cut system ensures a perfect cut and feeds the grass clippings directly into the collector. The ZD-Series offers you both comfort and speed of operation. With its powerful 25hp diesel engine and the high performance HST drive, this range meets the highest professional requirements.









F90-Series front mowers

Robust, comfortable and efficient, the F90-Series mowers meet the requirements of professional applications in all respects. Everything about these machines has been designed to make your working day as pleasant as possible. Designed for mowing large areas, the F-Series combines all the advantages that professionals demand: power, versatility, manoeuvrability and high productivity to ensure maximum savings and comfort in daily use. The practical optional extras are ideal for extending the range of applications that these tough machines can handle.

Pedigree horsepower you can rely on

With their impressive cutting performance, power and ease of operation, the new G-Series mowers let you tackle even the most demanding tasks with ease. Robust construction and legendary Kubota reliability complete the picture, setting new standards in this class.

#G-Series



Satisfaction is a job well done

The new G-Series is designed set new standards in its class. See for yourself the power of these machines, providing you with the performance you need to work efficiently and comfortably.

Fastest in its class

The opening and lifting speed of the grass collector is the highest in it's class. With a travel speed of up to 19 km/h, the mower is also best in class in terms of driving speed.

Simple operation with Kross Control

The Kross Control joystick enables you to operate both the mower and the grass collector. You use it to raise and lower the mower and to raise and open the grass collector. You can also use the joystick to close and lower the grass collector.

High-performance mowing, guaranteed

These mowers now offer even greater performance when cutting and collecting grass. The design features ensure that grass does not clump together as much and that the discharge channel is less likely to clog. The machines also have a higher power reserve.

High or low dump

The machine's large-volume grass collector works equally convincingly during high or low discharge.

Maximum performance under all conditions

The powerful HST gearbox guarantees high travel and working speed and impressive performance.

Highly efficient mowing

Whether the grass is tall or dense, wet or dry, the 122cm or 137cm cutting width of the mower deck guarantees high mowing performance in all conditions.

Model	Engine model	Power (hp)	Mower deck size cm (inch)	Grass collector
G231-LD-48	D902	22	122 (48)	Low dump (LD)
G231-HD-48	D902	22	122 (48)	High dump (HD)
G261-LD-54	D1005	25	137 (54)	Low dump (LD)
G261-HD-54	D1005	25	137 (54)	High dump (HD)

The right power for strong performance

The powerful Kubota engines provide the firm foundation for excellent mowing performance. Ease of maintenance and a large fuel tank also ensure short downtimes.

Efficient hydraulic system

The newly designed hydraulic system allows quick hydraulic operations like lifting and dumping the grasscollector.

#G-Series



High power for high performance

With 22hp or 25hp respectively, Kubota's hightorque diesel engines are the solid foundation for excellent mowing performance. With more muscle for the job, you can mow even high or wet grass effortlessly.



Maximum performance under all conditions

The powerful HST gearbox guarantees high travel and working speeds and impressive performance. This allows the machines to show their full strength.



Flawless cut and performance

The new G-Series mowers not only provide the best mowing performance in their class, but also trouble-free mowing. This is guaranteed by the ingenious grass flow between the machine and the grass collector, which prevents clumping.



Effortlessly collect and deposit grass

The mowers offer yet another benefit: no grass collector in their category can be raised and opened faster than theirs – another factor that increases productivity when mowing.

#Technical data

Model	G23	1	G261	
Engine				
Туре		Water-cooled, 3-cylinder diesel		
Model	Kubota I	0902	Kubota D1005	
Displacement cm	3 898		1,001	
Engine gross power (SAE 1995) hp (kW) 22 (1	6)	25 (19)	
Maximum operating engine speed rpr	n 3,240 to	3,390	3,270 to 3,420	
Fuel tank capacity	1	20		
Transmission				
Туре		Hydrostatic tran	smission	
Maximum travel speed (Forward) km/	19.0)	19.0	
Differential lock		Standar	d	
Cruise control		Standar	d	
Speed control		F/R 1 peo	dal	
Tyre size				
Front		16 × 7.5 – 8	3 Turf	
Rear		24 × 12.0 – 1	2 Turf	
Brakes				
Туре		Wet disc	0	
Steering				
Туре		Hydrostatic p	Dower	
Dimensions				
Tread Front mr	1	900		
Rear mr	ı	840		
Wheel base mr	ו 1,39	0	1,460	
Overall length (w/ G/C, w/ front weight bracket for HD) mr	3,100/3	,345	3,100/3,345	
Overall width with mower deck mr	n 1,26	5	1,420	
Overall height with rops	1	2,205		
Weight without fuel. With mover and GC LD/HD k	815/9	55	855/995	
Mower mounting				
Туре		Gear drive		
Clutch		Electromag	netic	
Others				
Water temperature gauge		Standar	b	
Overheating Alarm		Standard		
Fuel gauge		Standard		
Hour meter/Tachometer		Standard		
Easy checker		Standar	d	
Mower specifications				
Model	RCK48-	G231	RCK54-G261	
Cutting width cm (incl			137.2 (54)	
Mower drive method	,	Gear drive		
Mower lifting method		Hydraulic		
Mower lifting height mr	150			
Cutting height mm (incl		25 - 102 (1.0 - 4.0)		
Cutting height adjustment	Dial (1/4")			
Number of blades	2			
G/C				
Capacity (HD/LD)		640/560)	
Dumping height (HD) mr	1	1,970		
Sensor for G/C		Weight sensing		
Material of G/C bag (HD/LD)		Metal/Cloth		

The company reserves the right to change the specifications without notice. This brochure is for descriptive use only.

#G-Series



High performance, all day long

The G21E Series ride-on mowers provide impressive mowing performance and great comfort. This allows you to work in comfort all day long with high efficiency.

Powerful Kubota engine

The liquid-cooled Kubota diesel engine delivers plenty of power and torgue for even the toughest commercial jobs. With a top speed of 15 km/h, you can quickly move on to your next task.

Professional performance levels

This high-performance, robust ride-on mower is equipped with a number of innovative features, including Kubota's revolutionary "Glide Cut" system, which cuts and collects the grass. All machines are available with a high or low discharge grass collector.

Highly productive and profitable

The more efficient you are, the greater your profitability. The G21E Series ride-on mowers from Kubota enable you to achieve both. These machines will keep you highly productive all day long, which in turn translates into better financial results.

Parallel-Link system

The hydraulic Parallel-Link system lets you dump at variable heights (70-175 cm) without spilling. Adjust it lower to unload under trees and higher to unload onto truck beds.

HST Transmission

Kubota's shaft-driven HST transmission receives power directly from the engine and then transmits that power to the wheels via a gear train. This system maximizes durability, minimizes power loss, and ensures smoother and quieter operation.

Quick-clean System

Model	Engine model	Power hp	Mower deck size cm (inch)	Grass collector
G21E-LD	D782	21	122 (48)	Low dump (LD)
G21E-HD	D782	21	122 (48)	High dump (HD)

Versatile and durable

Kubota mowers offer you everything you need to successfully master a wide variety of tasks. Thanks to their durability and robustness, you will also be able to enjoy them for a long time.

Suspension seat/ Full-flat deck

A generously padded and contoured high-back seat easily adjusts to provide optimum driver comfort. The full-flat deck offers ample legroom to minimize fatigue.

Large-volume grass collector

A generous grass collector lets you work longer between stops to dispose of clippings. That means fewer stops — and more productive work time.



Now you can clear wet grass without even leaving the driver's seat. Just use one lever to clear a path to the grass collector. To clean the inside of the mower deck, simply connect a water hose to the cleaning pipe on each side of the deck, then run water while the mowing blade is rotating.

#Technical data

GLID	EGUT

The first "Glide Cut" mower and still the best

The first ride-on mowers to feature a three-blade, reardischarge cutting deck that both cuts and collect the grass. Unlike other three-blade side discharge turbinepowered collecting systems, "Glide Cut" cuts and channels the grass into the integrated rear grass collector. Because "Glide Cut" does not require a duct on either side of the cutting deck, tight turns can be made in both directions. And with a generous 48" cutting width, "Glide Cut" leaves smaller gaps of uncut grass when cutting around trees. "Glide Cut" cuts the toughest jobs down to size.



Pro deck

Upgraded for cleaner cutting and collecting, the Pro deck features a 25 mm front slit that greatly increases suction while preventing grass from being pushed down. An air-intake on top further enhances suction. Reduced clearance between the cutting blade and the vacuum plate prevents grass clippings from adhering to the plate. An extended jump plate prevents clippings from falling to the ground.



Heavy-duty ladder frame chassis

Kubota's unique ladder frame chassis is exceptionally rugged and durable, with superior torsional rigidity under even the most extreme conditions. A rigid stamped steel mower deck and heavy-duty transaxle further enhance durability.

Model	G21E LD	G21E HD		
Engine				
Model	Kubota	a D782		
Туре	Liquid-coc	led, diesel		
Total displacement cm	77	78		
Engine gross power (SAE 1995) kW (hp	15.6	(20.7)		
Maximum operating engine speed min. (PTO ON) rpn	3050-	-3200		
Number of cylinders	5	3		
Capacity				
Fuel tank	2	2		
Mower mounting				
РТО	Shaft			
PTO clutch	Belt te	ension		
Tyre size Front mn	16 x			
Rear mn	23 x 1	U.U-1Z		
Steering	Mar	buol		
Brake	- IVidi			
Brake	Internal expa	anding brake		
Transmission				
Travel speed control	Foot	pedal		
Transmission	Hydro			
Speed Front km/l	0-15			
Rear km/l	0.			
Dimensions				
Overall length (with grass catcher) mn	2,950	2,990		
Overall width (with mover) mn	1,2	80		
Overall height mn	2,0	65		
Wheelbase mn	1,2	90		
Tread Front mn	82	25		
Rear mn	78	30		
Weight (without mover) kg	610	650		
Mower				
Model	RCK48G1			
Cutting width mn	1,220			
Cutting height mn	25-102			
Cutting height adjustment	Dial gauge			
Mounting method	Quick joint, parallel linkage			
Weight kg	95 Direct du te			
Discharge type Direct chute				
Grass collector				
Model	GCK500-2	GCK500HD-2		
Container capacity	50			
Dumping height mn	-	1,750		

The company reserves the right to change the above specifications without notice.

#ZD-Series



Makes work a pleasure

Kubota developed the ZD-Series zero-turn mowers for professionals who need to achieve top results every day. Extreme manoeuvrability, ease of operation and maintenance and – last but not least – the impressive large-area performance of these mowers make your work easier.

Excellent mowing quality

The ZD-Series mowers leave a clean lawn without clumps of grass. Mulch quality is one of the best on the market.

Extremely nimble and powerful

This mower is able to turn on the spot. For strong performance in all conditions, the Kubota diesel engine provides all the torque you need.

Easy to operate

All you need to do is get on this mower and you are ready to go. All controls are within easy reach and intuitive to operate.

Exceptionally comfortable

Simple maintenance

The large operator's seat with integrated armrests ensures exceptional comfort ideal for long working days.

Powerful Kubota diesel engines

The modern diesel engines offer unparalleled power, productivity and fuel economy, even during demanding mowing jobs.

New low-profile tyres

The low-profile tyres on the rear axle further improve the stability and traction of the ZD-Series on lawns. Thanks to their large tread area, they also protect the lawn from damage during mowing.

Transmission with shaft drive

Kubota's large-volume, shaft-driven hydrostatic transmission features a smooth, guiet and maintenance-free axle drive. Power is transmitted via a shaft directly from the engine to the transmission and from there to the tyres via a toothed gear.

Optional mulching equipment

When you need to check the mowing unit, simply lift the entire machine into the service position. The engine cowling is simple to open and provides easy access to all important service points.



Long operating times

The 49L fuel tank enable long periods of mowing without refuelling.

User-friendly and comfortable

The comfortable operator's platform is equipped with a large driver's seat. All control functions are easily accessible and simple to operate.

Hydraulic mower deck lift

The hydraulic mower deck lift is operated with two pedals. Because you can raise and lower the mower unit with your foot, you can easily continue mowing regardless of obstacles.

Outstanding driving stability

With a 152 cm rear discharge, the ZD-Series mowers are also available with optional mulching equipment.

The low centre of gravity allows you to work safely. Together with the large rear wheels, long wheelbase and fuel tanks positioned above the tyres and under the seat, the ZD-Series provides excellent driving stability.

#ZD-Series

#Technical data



Large and bright new LCD display

The generous LCD display - the largest in its class presents all the essential information you need to maximise cutting performance, including oil pressure, water temperature, fuel level and voltage. The hour meter keeps you informed of upcoming maintenance and service intervals.



New ergonomically arranged controls

For faster operation and better ergonomics, all the mower's controls are within reach of your right hand, allowing you to quickly and easily adjust the cutting height. It is also very easy to see the cutting height setting, which further simplifies adjustment work.

Tilt-up system for easy maintenance

With Kubota's innovative two-bolt tilt-up system, routine maintenance under the mower is quick and easy. All you need to do is lift the front of the mower, to have an easy access to the blades.



Mower unit with rear discharge

The rear discharge system generates a uniform airflow, which ensures that all the cut material is ejected homogeneously. It can be fitted with an optional mulching kit.

New mulching equipment (option)

Kubota has redesigned the mulching equipment to produce even finer cuttings that are evenly distributed across the lawn. The result is a clean lawn that saves you time as well. The mulching equipment can be attached to both rear and side discharge mowers.

Model		ZD1211		
Engine				
Туре		Liquid-cooled, 3-cylinders diesel		
Model				
Engine gross power @ 3000	rpm (SAE 1995) hp (kW)	25 (18,5)		
Displacement	cm ³	1,123		
Air cleaner indicator		Standard		
Fuel tank capacity	1	49		
Transmission	· · ·	2 HST with integrated transaxle		
Tyre size				
Front		15 × 6.5 – 8, smooth semi-pneumatic		
Rear		$26 \times 12.0 - 16$ turf, low profile tyre		
Travelling speed range				
Forward	km/h	0 - 17.0		
Reverse	km/h	0-8.5		
Dimensions	KII/II	0 = 0.0		
		2,260		
Overall length Overall width with move	r mm			
		1,875 (side)/1,600 (rear)		
Overall height Rops uprig		2,000		
Rops folde		1,640		
Wheelbase	m	1,440		
Tread Front	mm	1,064		
Rear	mm	1,210		
Weight with mower (w/o fu	el) kg	790		
Mower deck				
Discharge direction		Side/rear/mulching (available as option for both side and rear)		
Mower deck construction		Fabricated		
Deck depth	mm	140		
Deck stell thickness	mm	4.2		
Mower lift system		Hydraulic lift by foot pedal		
Mower deck drive system		Shafl Drive		
Anti-scalp roller		Caster x 2, rigid x 4		
Cutting width	cm (inch)	152 (60)		
Cutting height adjustment		Dial		
Cutting height range	mm	25-127		
Cutting height increments	inch	0.25		
Number of blades		3		
Front axle		Selective ,Fix' and ,Oscillating' front axle		
Maintenance lift system		Standard		
Display		LCD panel (hour meter, fuel gauge, coolant temperature gage, battery voltage met)		
Seat		High back deluxe seat with reclining and lumbar support		
Seat suspension stroke	mm	76		
Step open system for easy	maIntenance	Standard		
Rops		Foldable		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional, and not standard equipment. Please contact your local Kubota dealer for warranty, safety or product information.

Top performance and unparalleled manoeuvrability – with the GZD-Series builds on Kubotas legacy of ultra efficient zero turn mowers with grass collector that combine the best of two worlds for increased productivity: the ability to turn on the spot and the ultra-efficient Glide Cut mower deck with integrated grass collector.

The best reward is heartfelt thanks



#GZD-Series



Performance and results in perfect harmony

Thanks to their excellent manoeuvrability, GZD-Series mowers meet the needs of both experienced and novice mowing specialists. These zero-turn diesel mowers combine exceptional manoeuvrability with an extremely efficient direct grass collection system with low or high discharge.



Unique on the market Only Kubota offers a zero-turn mower with direct transfer of the clippings into the grass collector, like the machines of the GZD-Series.

Glide Cut mower deck with large grass collector

Kubota's Glide Cut system cuts the grass and guides it directly into the integrated, large-volume grass collector at the rear.

Extremely agile and powerful The mower can turn on the spot. The Kubota diesel engine offers impressive levels of torque.

Large grass collector



Deep-drawn mower deck

Equipped with a deep-drawn mower deck (123.4mm inside), the GZD21 zero-turn mower cuts faster - even tall, dense or wet grass can be easily tackled.

Easy to operate

Climb on, sit down, start mowing. All controls are intuitively arranged and easy to reach.

Compact dimensions

Thanks to their compact size and low weight, the GZD21 are easy to transport. Their cost-efficient features increase your profit by keeping operating costs low.

Large-capacity fuel tank

The large tank holds 19 litres of fuel. This saves valuable time when refuelling and enables you to mow longer without interruption.

Hydraulic high dump with parallel system

The practical parallel system moves the grass collector vertically, thereby even enabling discharge at variable heights (0.9m to 1.8 m) without spilling any grass. By lowering the system, you can also discharge grass under trees or other obstacles. When set to the maximum height of 1.8 m, you can also load grass onto truck beds.

Comfortable, ergonomic operator platform

The comfortable operator platform features a large seat. All controls are within easy reach and are simple to operate.

Lifting height of the mower deck

Using a pedal-operated hydraulic linkage, the mid-mounted mower deck can be quickly raised up to 135mm for increased ground clearance. It is just as easy to lower it again.

#GZD-Series

#Technical data



2-lever control

The independent left and right steering levers give the GZD21 zero-turn mower amazing maneuverability at the slightest touch - including a 360-degree turning radius.

Central cutting height adjustment

The cutting height can be easily adjusted from the operator's seat from 2.5-12.7cm via the central cutting height adjustment. You can also make fine adjustments.

Quick cleaning

The Quick Clean system effectively prevents blockages in the discharge channel. The channel can be easily cleaned from the operator's seat.



Mower deck with cardan shaft drive

When it comes to drive systems, shafts are still the most durable. That's why the mid-mounted mower deck on the zero-turn mower has a highly reliable and quiet shaft drive.



Transmission with cardan shaft drive

Kubota's large-volume, shaft-driven hydrostatic transmission features a smooth, quiet and maintenancefree axle drive. Power is transmitted via a shaft directly from the engine to the transmission and from there to the tyre via a toothed gear.

Wet multi-plate clutch and disc brakes in oil bath

Kubota's incomparable wet multi-plate clutch is so durable that it outlasts most others, while the oil-bath disc brake provides superior braking power for safer operation.

Model		GZD21-HD		
Engine				
Туре		Kubota D782		
Model		Liquid-cooled, 3-cylinders diesel		
Displacement	cm ³	778		
Engine gross power (SAE 1995)	hp (kW)	21 (15,6)		
Maximum operating engine speed	rpm	2,880-2,980		
Fuel tank capacity	I	19		
Tractor				
Mower position		Mid-mount		
Tyre size Front	mm	15 x 6.0-6		
Rear	mm	23.0 x 10.5-12		
Wheelbase	mm	1,285		
Overall length	mm	2,865		
Overall width	mm	1,280		
Overall height	mm	1,950		
Weight (with mover and GC, without fuel)	kg	640		
Drive train				
Speed Front	km/h	0-15.5		
Rear	km/h	0-11.5		
T/M drive system		Shaft drive		
Mower drive system		Shaft drive		
Drive system		2-HST		
Steering style		2-hand levers		
Parking brake		Wet multi-discs, mechanical equalising brake system		
Turning radius	m	0		
РТО				
PTO clutch		Hydraulic wet multi discs		
PTO brake		Hydraulic wet single discs		
Mower				
Cutting width	cm (inch)	121,9 (48)		
Lift system		Hydraulic		
Mount system		Parallel linkage		
Blade drive system		Hex belt, gear		
Cutting height	mm (inch)	25–127 (1–5)		
Cutting height adjustment		Dial		
Maximum mower lift height	mm	145		
Number of blades		3		
Grass collector				
Туре		High dump/hydraulic		
Capacity	1	500		
Maximum lift height	m	1.80		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

Kubota F-Series front mowers are the perfect machines to meet the needs of contractors and municipal users who value quality work, efficiency, reliability and comfort. It goes without saying that these mowers perform impressively over large areas.

The bigger the job, the greater the pleasure

#F-Series



At the end of the day, the best you can buy

Kubota's front mowers combine all the advantages that are important to professionals - power, versatility, manoeuvrability as well as high productivity and comfort to achieve optimum work results in daily use. The F-Series mowers give you all the features you need to get your mowing jobs done quickly and efficiently.

High impact

F-Series mowers are designed for high performance. This is enabled by mower deck widths of up to 1.82m, a high driving and working speed and the 61-litre fuel tank for long operating times.

Easy maintenance

You can fully open the engine cowling. This makes it easy for you to check the oil level, clean the air filter and remove dust from the radiator grille. The mowing deck can be pivoted upwards by 90° for easy washing, and blade changes are also straightforward - even in the field.

Versatility included

This machine is more than just a mower. It can be a mower (side discharge, rear discharge, mulching, grass collection), but it can also be equipped with a flail mower, leaf blower, snow blade, etc.

High level of comfort included

With a strong heart

The Kubota diesel engines deliver up to 38hp. This makes even heavy work a breeze, such as mowing and collecting high and wet grass.

Powerful on all paths

The on demand four-wheel drive (apart from the F2890) Gives great grip when mowing. The optional road homologation kit turns the mower into a road-legal vehicle.

The mower offers a variety of comfort features, including HST pedal, hydrostatic steering, comfort seat with air suspension (optional), ergonomically optimized driving position and on demand Four wheel drive.



Durable and safe

The stable "Made in Japan" chassis frame and rollover protection are synonymous with durability and safety. Safety is also guaranteed by the high-power wet disc brakes. To reduce maintenance costs, you only need to change the outer section of the double air filter. The inner element can be cleaned.

Comfortable and easy to operate

On the ergonomic operator platform, you have everything perfectly under control. The digital screen displays all information in an easily readable format. The optional air-sprung seat ensures even more riding comfort.

Reliable and dependable

The 14 cm deep mower deck is made from high strength steel. The drive system features multiple steel V-belt pulleys and are extremely durable. Kubota has also developed a robust flail mower especially for mulching high grass and undergrowth.

#F-Series



Comfortable year-round use With the optional comfort cabin, you're perfectly protected from the weather – whatever the season.

Grass collector

You can equip the machine with 900-litre grass collector. The GCD900P has a hydraulic drive. High-flow turbines enable perfect grass collecting.



For perfect mulch

With the optional mulching equipment, you can convert the rear or side discharge mower deck into a precision mulching system that produces particularly fine mulch.



Extended range of applications

A high-quality front linkage further extends the mowers' range of applications. For example, this enables you to mount attachments like flail mower.



Turning into a road-legal vehicle

The machines can be converted into a road-legal vehicle by means of a road homologation kit. This option is particularly useful where long distances need to be covered between locations as quickly as possible.

#Technical data

Model			F2890E/2WD	F3090/4WD	F3890/4WD	
Engine						
Model			Kubota D1105	Kubota D1305	Kubota V1505	
Туре				3-cylinder diesel	Liquid-cooled, 4-cylinder diese	
Engine gross power (SA	E 1995)	hp (kW)	28 (20,6)	30 (22,4)	38 (27,8)	
Rated revolution		rpm	- (- / - /	3,000		
Displacement		cm ³	1,123	1,261	1,498	
Fuel tank capacity		1	.,	61	.,	
Transmission						
Туре				HST (F2/R2)		
Maximum travell speed	Forward	km/h		20		
	Reverse	km/h		11		
4WD/2WD			2WD		4WD	
4WD mode select			N/A	Full-time 4WD or auto-assist 4V	VD, with dual acting overrunning clute	
Differential lock				Standard	· · · · · · · · · · · · · · · · · · ·	
Cruise control				Optional		
Travelling speed		km/h		0–20		
Steering						
Steering system				Hydrostatic power steering		
Tilt steering				Standard		
Tum assist brake				Optional		
Turning radius		mm		750		
Tyres*						
Front			23 x 10.5-12	24	x 12.0-12	
Rear			16 x 6.5-8		8 x 9.5-8	
Dimensions			10 x 0.0 0			
Wheelbase		mm		1,300		
Overall length without d	eck	mm		2,450		
Overall width without de		mm	1,240	2,100	1,370	
Overall height ROPS up		mm	1,210	1,985/1,350	1,010	
Weight w/o mowerdeck		kg	720	765	775	
Mower deck		itig	120	100	110	
Drive system		cm (inch)		Shaft drive		
Clutch type		GITT (ITIOT)	Wet multi discs, hydraulic			
Mounting system			2	-piont hitch with hydraulic lift cyl	inders	
PTO revolution		rpm		2,545		
Deck tilt angle		۰ ۱۶۱۱		90		
Deck tilt assist				Standard		
Maintenance				Otalidard		
Air cleaner	Dust indicator			Standard		
	Dual element			Standard		
Tool box	Buarciement			Standard		
Operator				Standard		
Seat	Armrest adjust			Standard		
Jean	Beckrest adjust			Standard		
	Reclining			Standard		
Cup holder	Reclining			Standard		
Hydraulic				otanuaru		
Rear hydraulic outlet (1	speel)			Optional		
Rear hydraulic outlet (2	· ·			Optional		
near nyaraano oadiet (2	30001)			Optional		
Mower specifications						
Cutting width	Side discharge	cm (inch)	137 (54)/152 (60)	152/	(60)/182 (72)	
	Rear discharge	cm (inch)	152 (60)		(60)/182 (72)	
Mulching kit	Side discharge	0.11 (1101)	.02 (00)	Optional		
	Rear discharge			Optional		
Cutting height minimum		mm (inch)	25 (1)/129 (5)			
Cutting height adjustme		mm (inch)	Each 6.4 (0.25)			
Grasscollector specifica	ations					
Model			GCD900U		GC900P	
Capacity		1		850		
Dumping height		mm		2,200		
			Belt driven		Hydraulic driven	

* other optional tyre combinations available

Kubota (U.K.) Limited

Dormer Road Thame, Oxfordshire, OX9 3UN

http://www.kubota.co.uk

This publication may not be reproduced in whole or in part in any form without the prior written consent of KUBOTA. It corresponds to the status at the time of going to press. The manufacturer reserves the right to change technical specifications without notice. Some of the parts shown in the publication are optional and are not part of the standard equipment. Information on warranty and safety as well as further product information can be obtained from the responsible KUBOTA authorized dealer.