



KUBOTA FRONT MOWER

A versatile front mower with Foot-Control 4WD

F1900

Easily Engaged, Foot-Control Puts 4WD At Your Feet



The F1900's compact design provides manoeuvrability in tight corners where larger front mowers cannot go. And its range of work areas is increased with Kubota's bevel gear 4WD system. This provides a tight turning radius and delivers smooth power transfer to the wheels, even during sharp turns.

- For ground-hugging continuous traction on slopes or in slippery conditions, you can swiftly lock in 4WD on-the-go by depressing the 4WD Lock Pedal. Return to 2WD with a simple touch to the 4WD Release Pedal.
- To help you power through a tough spot, temporary "on-demand" 4WD is easy—just press and hold the two designated pedals simultaneously—the 4WD will disengage when you release the pedals.
- The F1900 is powered by a 3 cylinder, 18 horsepower, liquid cooled, Kubota diesel engine. The hydrostatic transmission eliminates shifting and clutching; speed and forward/reverse changes are controlled by the same single foot pedal.
- Two shaft driven mower decks are available: 48" and 54" side discharge mowers.
- The F1900 with 4WD has the performance features needed to get your mowing jobs done quickly and efficiently.



**ROPS (Safety Frame) is optional.*

SPECIFICATIONS

MODEL	F1900	
ENGINE		
Model	D722	
Type	Water-cooled Diesel Engine	
Max. Horsepower	13.4 kW (18 HP) / 3,200 rpm	
No. of Cylinders	3	
Total Displacement	719 cc	
Mounting	Rubber Mounting	
FUEL TANK	Capacity	20 lits.
	Indicator	on Front Panel
TIRE SIZE	Front	20 x 10—8
	Rear	16 x 6.5—8
DIMENSIONS		
Overall Length	[with 54 inch Mower Deck installed]	1,950 mm [2,330 mm] (76.8 in. [91.7 in.])
Overall Width	[with 54 inch Mower Deck installed]	970 mm [1,737 mm] (38.2 in. [68.4 in.])
Overall Height*		1,200 mm (47.2 in.)
Wheel Base		850 mm (33.5 in.)
Wheel Tread	Front	718 mm (28.3 in.)
	Rear	795 mm (31.3 in.)
WEIGHT (without mower)		490 kg (1080 lbs.)
TRANSMISSION	HST	
Travelling Speed	(F) 0—13.5 km/h (0—8.4 mph)	(R) 0—6.5 km/h (0—4.1 mph)
Speed Control	1 Foot Pedal + Cruise Control	
TRACTION	Front based On-Demand 4WD	
STEERING	Rear Wheel	
Tilt Steering	Standard	
PTO CLUTCH	Hydraulic	
PTO BRAKE	Wet Disc	
MOWER DECK		
Lift System	Hydraulic	
Driving by	Shaft	
Cutting Width	1,220, 1,370 mm (48, 54 in.)	
Cutting Height	25—102 mm (1—4 in.)	
OTHERS		
Seat Adjustment	One-touch	
Step Deck	Semi-flat	
Water Temp. Meter	Meter on Front Panel	
Hour Meter	Standard on Front Panel	

*When the tilt steering is set at its highest position.
Specifications are subject to change without prior notice.

©2007 Kubota Corporation

Kubota

KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN,
Phone Thame (01844) 214500 Fax (01844) 216685
Web site: <http://www.kubota.co.uk/>
E-mail: sales@kubota.co.uk

Cat.No.2153-01-UK Printed in Japan D. REX.'07-JUN.